



PTX500 5-foot, Tractor PTX600 6-foot, Tractor PTX700 7-foot, Tractor

25hp to 35hp Small-Frame & Mid-Frame Tractor

The TX Series is uniquely designed for use with 25-35hp compact tractors. Introducing the 5-foot PTX500, 6-foot PTX600 & 7-foot PTX700. The TX Series offers the performance, durability and compatibility needed for 25-35hp compact tractors.

## **INDUSTRY EXCLUSIVE**

*Quick Change Rotor and* 3 Rotors to choose from. 2" Sabre Tooth, 1 3/4" Carbide Aggressor, Flat Bar/Processing Rotor

## Specifications

Mainframe:	1/4" X 3" X 3" Structural Steel Frame
Gauge Wheels:	Flip-up, Adjustable, Removable
Drive:	540 RPM PTO
Drive Chain:	#80 Single Roller Chain and Self-Adjusting Tensioner
Mount:	Cat 1 3-Point Hitch
Side Shields:	Quick-flip, Standard Equipment
Angle:	Left, Right and Straight, Standard Equipment
Angle:	Manual Angle or Hydraulic Angle
Materials Bar:	Adjustable, Standard Equipment
Protection:	Slip Clutch or Shear Pin
Rotor Bearings:	Triple Seal Rotor Bearing
Rotor Brg.Housing:	Steel Cut & Replaceable
Rotors:	Sabre Composite Metal Tooth
	Aggressor Carbide Tooth
Special Rotor:	Processing or Rotary Broom



Operate in Landscaping Mode:	Yes
Operate in Tilling Mode:	Yes
Greaseable Rotor Bearings:	Yes
Quick-Tach Rotors:	Yes
Adjustable Hitch Pins In/Out	Yes
Ridge or Float Center Link	Yes
Material Bar Safety Slider:	Yes
High Folation Rear Tires:	Yes

Option's Material Side Shield Ski/Shoe Yes

## What it does

PIRANHA is a piece of equipment that makes landscaping quick and easy. The rotor turns in a counter-rotating motion, putting rock and debris between the end shields while processing the dirt through the machine, leaving an excellently prepared seed bed. Operating the PIRANHA with the gauge wheels down puts the PIRANHA in the landscaping mode. Operating the PIRANHA with the gauge wheels in the "up" position puts the machine in the tilling mode. Flip up the end shields and angle the PIRANHA to windrow rock and debris either by manual or hydraulic turn.

/w.nortecmfg.com

For More Information Call 715-623-6300 Ask For Product Support Center